E-Series Technical Specifications



Product Description:

24/7 OSC "E-Series" units are designed to meet the rugged demands of the construction site rental market. The "E-Series" units have over 10 years of Mobile Camera System manufacturing built into them. Each system is designed for easy deployment, 24/7 usage, advanced analytics and with the highest quality high mega pixel cameras. Each unit is designed to be self sufficient and self report any technical problems it may experience. These machines have changed the industry standard for Mobile Camera system deployment.

Product Features:

- Industrial Rental rugged design
- · Easy to deploy
- Advanced analytics
- Onboard Redundant hard drive storage
- 750amp/hr of AGM Storage batteries
- Manual Winch
- 25' Mast height
- Onboard "monitoring ready" analytics
- 4G LTE Cellular router
- 3MP PTZ cameras w/30 x zoom
- Talk down feature

Applications:

Industrial, Manufacturing, Construction Entertainment State and Federal Law Enforcement DOT's, Traffic monitoring FEMA, TSA, Emergency management Oil and Gas Colleges/Universities

Specifications:

Stowed: 176.4"(14' 7") L x 82.8"(6'9") W x 113"(9'4") H Deployed: 176.4"(14'7") L x 141"(11.75") W x 295"(24'6") H Weight: 2,740lbs Outriggers: Adjustable Hitch: 2" ball Axles: 1 Cameras: 4 x 3MP IP 30x Zoom Nighttime Lighting: 4 x 300' IR Illuminators w/photocell Offsite Remote Controls: Auto ping 8 point controller 1 Router-auto ping with auto reboot if ping fails 2 Cameras with remote on/off 3 IR Illuminators with remote on/off 4 NVR with remote on/off 5 Strobes with remote on/off 6 Analytics device with Remote on/off 7 Network switch with remote on/off 8 Spare

Batteries: 3 x 250amp/hr AGM batteries Connection: Cellular Router 4G LTE Low Voltage Disconnect: BG-40 with auto reconnect Control Housing: Lockable Equipment Panel: Thermostatically controlled fan Mast Cable: Molded Spiral Nycoil Talk Down: Valcom Speaker Strobes: Red/Blue LED w/photocell NVR: 8Ch with 4TB HDD Analytics: Checkvideo CV4IP with 6TB HDD Voltage regulator: Victron Energy Isolated AC/DC Converter Operating Voltage: 12V Inverter Voltage: MorningStar SureSine-300 Inverter Input 12V Output: 115vac Land power charging: Iota 55amp IQ Smart charger